

SHORE MATE®

FIRST BY DESIGN

BOAT LIFTS & DOCKS

Specification Sheet

Lift Model: L12000H

Weight Capacity:	12000#	Type of Lift:	Cantilever/HYD.
Maximum Beam:	144"	Application:	Sport / Cruise
Weight	1490#	Lift Dimensions:	237" L x 152" W
Lifting Height:	63"	Foot Pad Dim:	18" L x 15" W
Min. Water Depth:	26" Plus Draft	Leg Length:	48"
Power Source:	12V DC	Bunk Length:	18'

Standard Equipment:

18' Pivoting Vinyl Bunks
Battery Connector Cables (Battery Not Included)
Beam 144"
Hydraulic Pump w/ Quick Connect Hoses, Pre-Charged Lines and Fluid
Stainless Steel Fasteners
(2) 4" Stainless Steel Cylinders w/ Brass Rod Scrapers
48" Lift Legs (Set of 4)
All Aluminum Frame
Hand Control Unit w/ Extended Cord
Lockable and Durable "Poly Hopper" for Pump and Battery Storage

Accessories:

Lift Legs: Longer Per Foot
Lift Transport Kit
Vertical Load Guides
20' Side Step Guides
Radio Remote Control w/ 2 Key Fobs
Solar Panel: 20 Watt
Solar Panel Holder (Mounts to Upright)
AC Charge Pack (In Place of Solar Panel)

Part #

LSA0251
LSA0020
LSA1121V
LSA1120
LSAH020
LSAH014
LSAH017
LSAH100

**Pontoon Conversion Kit: Center or Bunk
Tri-Toon Kit
Underwater Light Kit: New Lifts Only
Canopy**

**LSA0122
LSA0130
LSAH016**