

SHORE MATE®

FIRST BY DESIGN

BOAT LIFTS & DOCKS

Specification Sheet

Lift Model: L1200H

Weight Capacity:	1200#	Type of Lift:	Cantilever/ HYD.
Maximum Beam:	60" / 80"	Application:	PWC
Weight	180#	Lift Dimensions:	132" L x 66" W
Lifting Height:	32"	Foot Pad Dim:	12" L x 6" W
Min. Water Depth:	16" Plus Draft	Leg Length:	24"
Power Source:	12V DC	Bunk Length:	8'

Standard Equipment:

8' Pivoting Vinyl Bunks
Battery Connector Cables (Battery Not Included)
Beam 60" / 80"
Hydraulic Pump w/ Quick Connect Hoses, Pre-Charged Lines and Fluid
Stainless Steel Fasteners
(1) Stainless Steel Rod High Performance Cylinder
24" Lift Legs (Set of 4)
All Aluminum Frame
Hand Control Unit w/ Extended Cord
Lockable and Durable "Poly Hopper" for Pump and Battery Storage

Accessories:

	<u>Part #</u>
Lift Legs: Longer Per Foot	LSA0251
Lift Transport Kit	LSA0020
Radio Remote Control w/ 2 Key Fobs	LSAH020
Solar Panel: 10 Watt	LSAH014
Solar Panel Holder (Mounts to Upright)	LSAH017
AC Charge Pack (In Place of Solar Panel)	LSAH100