

SHORE MATE®

FIRST BY DESIGN

BOAT LIFTS & DOCKS

Specification Sheet

Lift Model: L1200HD

Weight Capacity:	1200#	Type of Lift:	Cantilever/ HYD.
Maximum Beam:	114" / 120"	Application:	PWC
Weight	350#	Lift Dimensions:	132" L x 120" W
Lifting Height:	32"	Foot Pad Dim:	12" L x 6" W
Min. Water Depth:	16" Plus Draft	Leg Length:	24"
Power Source:	12V DC	Bunk Length:	8'

Standard Equipment:

8' Pivoting Vinyl Bunks

Battery Connector Cables (Battery Not Included)

Beam 114" / 120"

Hydraulic Pump w/ Quick Connect Hoses, Pre-Charged Lines and Fluid

Stainless Steel Fasteners

(2) Stainless Steel Rod High Performance Cylinder

24" Lift Legs (Set of 4)

All Aluminum Frame

Hand Control Unit w/ Extended Cord

Lockable and Durable "Poly Hopper" for Pump and Battery Storage

Accessories:

Lift Legs: Longer Per Foot

Lift Transport Kit

Radio Remote Control w/ 2 Key Fobs

Solar Panel: 10 Watt

Solar Panel Holder (Mounts to Upright)

AC Charge Pack (In Place of Solar Panel)

Part #

LSA0251

LSA0020

LSAH020

LSAH014

LSAH017

LSAH100