

SHOREMATE®

FIRST BY DESIGN

BOAT LIFTS & DOCKS

Specification Sheet

Lift Model: L30000H

Weight Capacity:	30000#	Type of Lift:	Cantilever/HYD.
Maximum Beam:	168"	Application:	Sport / Cruise
Weight	#2750	Lift Dimensions:	TBD
Lifting Height:	63"	Foot Pad Dim:	18" L x 15" W
Min. Water Depth:	26" Plus Draft	Leg Length:	48"
Power Source:	12V DC	Bunk Length:	(6) 8'

Standard Equipment:

(6) 8' Pivoting Vinyl Bunks
Battery Connector Cables (Battery Not Included)
Beam 168"
Hydraulic Pump w/ Quick Connect Hoses, Pre-Charged Lines and Fluid
Stainless Steel Fasteners
(4) 4" Stainless Steel Cylinders w/ Brass Rod Scrapers
48" Lift Legs (Set of 4)
All Aluminum Frame
Hand Control Unit w/ Extended Cord
Lockable and Durable "Poly Hopper" for Pump and Battery Storage

Accessories:

	<u>Part #</u>
Lift Legs: Longer Per Foot	LSA0251
Lift Transport Kit	LSA0020
Vertical Bumpers	LSA1120
Radio Remote Control w/ 2 Key Fobs	LSAH020
Solar Panel: 20 Watt	LSAH014
Solar Panel Holder (Mounts to Upright)	LSAH017
AC Charge Pack (In Place of Solar Panel)	LSAH100
Underwater Light Kit: New Lifts Only	LSAH016

Canopy